

University of Parma Research Repository

Computational fluid dynamics (CFD) modelling and experimental validation of thermal processing of canned fruit salad in glass jar

This is the peer reviewd version of the followng article:

Original

Computational fluid dynamics (CFD) modelling and experimental validation of thermal processing of canned fruit salad in glass jar / Cordioli, Matteo; Rinaldi, Massimiliano; Copelli, Gabriele; Casoli, Paolo; Barbanti, Davide. - In: JOURNAL OF FOOD ENGINEERING. - ISSN 0260-8774. - 150:(2015), pp. 62-69. [10.1016/j.jfoodeng.2014.11.003]

Availability: This version is available at: 11381/2783476 since: 2018-04-16T10:31:12Z

*Publisher:* Elsevier Ltd

*Published* DOI:10.1016/j.jfoodeng.2014.11.003

Terms of use:

Anyone can freely access the full text of works made available as "Open Access". Works made available

Publisher copyright

note finali coverpage

Elsevier Editorial System(tm) for Journal of Food Engineering Manuscript Draft

Manuscript Number: JFOODENG-D-14-00230

Title: Computational Fluid Dynamics (CFD) Modelling and Experimental Validation of Thermal Processing of Canned Fruit Salad in Glass Jar

Article Type: Research Article

Keywords: CFD; Thermal processing; Canned fruit salad; Natural convection; Conduction.

Corresponding Author: Prof. Davide Barbanti,

Corresponding Author's Institution: University of Parma - Italy -

First Author: Matteo Cordioli

Order of Authors: Matteo Cordioli; Massimiliano Rinaldi; Gabriele Copelli; Paolo Casoli; Davide Barbanti

Abstract: In this study, samples of commercial fruit salad (five different fruits with various geometries and thermal properties) were used for the experiments in order (i) to study the thermal behaviour of fruits during the heat treatment and (ii) to develop a computational fluid dynamics model to investigate the temperature profiles during samples processing. Simulation data were validated with the experimental ones obtained by means of a pilot plant. Results showed a good fit between theoretical and experimental data, both for syrup and fruit pieces. Experimental F values varied as a function of the type of fruit, its position, dimension and thermal property and they were shown to be influenced by the natural convection motion of the syrup. The proposed model can be used for the simulation and prediction of thermal processes of canned fruit salad, though better reliability (by reducing the differences between theoretical and experimental data and by studying the influence of fruit position inside the jar during the thermal process) can be achieved.



# UNIVERSITIA DEGLI STUDI DI PARMA DIPARTIMENTO DI SCIENZE DEGLI ALIMENTI Department of Food Science

www.unipr.it

Parco Area delle Scienze, 47/A 43124 Parma - Italia Tel. +39 0521 90 5706

To: Editor-in-Chief of Journal of Food Engineering

Dear Professor,

I would like to submit to your attention a reseach paper on "Computational Fluid Dynamics (CFD) Modelling and Experimental Validation of Thermal Processing of Canned Fruit Salad in Glass Jar", by *M.Cordioli, M.Rinaldi, G.Copelli, P.Casoli and D.Barbanti*, for the publication in the Journal of Food Engineering.

As reported in the instruction for authors, the manuscript has been deeply reviewed by a native English speaker.

Each decision and suggestion from you and referees will be useful to us in order to improve the scientific quality of the paper.

Parma, 02.25.2014

With my Best Regards

Davide Barbanti

Barhaut, Maude

# Highlights

Heat distribution was optimized during thermal treatment of fruit salad

A computational fluid dynamics model was used to investigate the temperature profiles

Simulation data were validated with those of experimental trials

The CFD model can be used for the simulation and prediction of thermal processes

1	Computational Fluid Dynamics (CFD) Modelling and Experimental Validation of Thermal
2	Processing of Canned Fruit Salad in Glass Jar
3	
4	Matteo Cordioli <sup>1</sup> , Massimiliano Rinaldi <sup>1</sup> , Gabriele Copelli <sup>2</sup> , Paolo Casoli <sup>2</sup> , Davide Barbanti <sup>1</sup> *
5	
6	<sup>1</sup> Department of Food Science, University of Parma, Parco Area delle Scienze 47/A, 43124 Parma,
7	Italy
8	<sup>2</sup> Department of Industrial Engineering, University of Parma, Parco Area delle Scienze 181/A,
9	43124 Parma, Italy
10	
11	
12	
13	*Corresponding author: Davide Barbanti, Department of Food Science, Parco Area delle Scienze
14	47/A, 43124 Parma, Italy. Tel: 0039-521-905706; e-mail: davide.barbanti@unipr.it

# 15 Abstract

16 In this study, samples of commercial fruit salad (five different fruits with various geometries and 17 thermal properties) were used for the experiments in order (i) to study the thermal behaviour of 18 fruits during the heat treatment and (ii) to develop a computational fluid dynamics model to 19 investigate the temperature profiles during samples processing. Simulation data were validated with 20 the experimental ones obtained by means of a pilot plant. Results showed a good fit between 21 theoretical and experimental data, both for syrup and fruit pieces. Experimental F values varied as a 22 function of the type of fruit, its position, dimension and thermal property and they were shown to be 23 influenced by the natural convection motion of the syrup. The proposed model can be used for the 24 simulation and prediction of thermal processes of canned fruit salad, though better reliability (by 25 reducing the differences between theoretical and experimental data and by studying the influence of 26 fruit position inside the jar during the thermal process) can be achieved.

- 27
- 28
- 29

30 Keywords: CFD, Thermal processing, Canned fruit salad, Natural convection, Conduction.

#### 31 **1.Introduction**

32 In the food industry, a great number of fruits and vegetables are packaged in cans or jars, filled with 33 an appropriate sugar syrup or brine, and thermally processed in order to increase their shelf life 34 through the inactivation of both spoilage microorganisms and enzymes (Kiziltas et al., 2010).

Heat transfer mechanisms in canned food are conduction for solid and high viscosity liquid foods,
natural convection for low viscosity liquid foods, convection plus conduction for liquid foods with
solid particles and convection followed by conduction for liquid foods containing starch or viscosity
modifiers (Chen and Ramaswamy, 2007).

39 Moreover, it is widely known that quality as well as nutritional characteristics of foods can be 40 dramatically reduced by the thermal stabilisation processes. Hence, time and temperature 41 combination during the heating and the cooling cycles must be properly assessed to guarantee both 42 effectiveness (inactivation of microorganisms and enzymes) and efficiency (retention of sensory 43 and nutritional characteristics as well as limiting of costs). As a consequence, the thermal process 44 must be properly designed by studying the thermal properties of foods and the mechanism of heat 45 transfer during the treatment. These purposes are normally achieved by a relevant number of 46 experimental trials with an increase in costs and time consumption thus reducing the possibility to 47 have fast, efficient and in-depth results (Sun, 2007).

In order to overcome these limits, in the last years, process design in the food industry has been
increasingly carried out by using numerical solutions of process governing equations, modelling
and calculation methods (Weng, 2005).

Among these, Computational Fluid Dynamics (CFD), has found widespread application in many areas of food processing such as spray drying, baking, sterilization, heat exchangers design, chilling, mixing, fermentation and in the agri-food industry (Sun, 2007).

54 CFD is a simulation tool which uses powerful computers and applied mathematics to model fluid 55 flow situations for the prediction of heat, mass, momentum transfer and optimal design in industrial

56 processes (Xia and Sun, 2002; Kuriakose and Anandharamakrishnan, 2010; Anandharamakrishnan, 57 2011; Chhanwal et al., 2012). Several works deal with CFD simulations of canned foods: Kumar et 58 al. (1990) simulated the natural convection in canned thick viscous liquid foods; Ghani et al. 59 (1999a, 2002) studied the natural convection heating of canned foods in vertical and horizontal 60 positions, showing faster heating in the vertical can, which is expected due to the enhancement of 61 natural convection caused by its greater height. The effect of the inclination of container walls and 62 geometry modification on the sterilization process was also investigated by Varma and Kannan 63 (2005).

64 A few works have been published on the CFD simulation studies of canned foods with solid/liquid 65 mixture. These include heat transfer and liquid flow prediction during the sterilization of large 66 particles in a cylindrical vertical can (Rabiey et al., 2007) and the heat transfer in canned peas under 67 pasteurization (Kiziltas et al., 2010). Ghani and Farid (2006) analysed and successfully modelled 68 the thermal sterilization process of canned solid-liquid food mixture (pineapple slices with 69 governing liquid) in metal cans, indicating that natural convection effects in the liquid played a 70 significant role in the evolution of temperature. In the same way, Dimous and Yanniotis (2011) 71 studied the temperature profile, the velocity profile and the slowest heating zone in a still can filled 72 with food items with cylindrical-conical shape such as asparagus. With regard to pineapples, 73 Padmavati and Anandharamakrishnan (2013) investigated the effect of size reduction of the product 74 (pineapple slices vs. tidbits) on the effectiveness of heat transfer during thermal processing.

However, the scientific literature still lacks a comprehensive simulation study for the prediction of temperature changes of solid-liquid mixtures where solids with different shapes and thermal characteristics are dispersed in the liquid phase.

In this paper, samples of commercial fruit salad (composed of five different fruits with various
geometries and thermal properties) were canned in glass jars and submitted to heat treatment.

The objectives of this work were (i) to study the temperature distribution and the thermal behaviour of both fruit pieces and syrup during the process and (ii) to develop and experimentally validate a computational fluid dynamics (CFD) model of the process itself.

83

#### 84 **2. Materials and Methods**

# 85 2.1 Plant and process details

86 The thermal treatment of fruit salad and sugar syrup in a glass jar was carried out in a small scale 87 static pasteuriser (JBT FoodTech, Parma, Italy), controlled by PLC. Inside the pasteuriser (width = 88 550 mm; length = 730 mm) water was sprayed over the containers from two nozzles at a rate of 2800 l\*h<sup>-1</sup> with a spread angle of 120°. Hot water temperature was set at 93°C and samples were 89 90 heated from 22 to 85°C at the slowest heating point (SHP). The water was heated and cooled 91 through a "tube in tube" heat exchanger where the heating and cooling media were water vapour 92 and icy water, respectively. The jar was positioned at the centre of the pasteuriser between the 93 nozzles and was surrounded with other jars (filled with the same product) in order to reproduce the 94 operating conditions of the industrial process.

95 During trials, only the heating phase of the thermal processing was studied.

96

# 97 2.2 Sample characteristics

The fruit salad was composed of five different fruits (percentage expressed by weight): peach (52%), pear (38%), pineapple (5%), grape (3%) and cherry (2%). Peach and pear were cubic with sides of 10 and 8 mm, respectively. Pineapple had a truncated pyramid geometry (such as a titbit, with a thickness of 5 mm and major edge of 10 mm). Cherry had a hemispherical geometry with a radius of 8 mm, with a spherical hole at the centre (due to destoning) with a radius of 4 mm. The grape had an ellipsoidal geometry, with major and minor axis of 8 and 5 mm, respectively (**Figure 1**). The fruits were inserted into the jar simulating an industrial filling process in the order peach,

pear, pineapple, grape and cherry. The jar was then filled with 16.7% (w/w) sucrose solution measured with an electronic refractometer (Sinotech, Fujian, China). The solid/liquid ratio was 61:39, the same as those of commercial samples. The jar used for the trials had a filling volume of 372 ml, diameter = 86.0 mm; height = 90.5 mm. Glass thickness was measured with a calliper at different locations on the side and bottom surfaces of the container and resulted in an average value of 3.5 mm. Prior to experiments, the jar was hermetically closed with a screw metal cap with a liameter of 85 mm.

112

## 113 2.3 Data acquisition

114 The temperatures inside the jar were measured using thermocouples (K-type; Ni/Al-Ni/Cr) 115 connected to a multimeter acquisition system (Yokogawa Electric Corporation, Tokyo, Japan). A 116 stainless steel multipoint temperature probe was positioned along the central axis of the jar through 117 a hole made in the centre of the cap. This multipoint probe (length = 97.5 mm; diameter = 3.5 mm) included four thermocouples spaced every 13 mm from the tip of the probe in order to record the 118 119 syrup temperature at four different heights (17.5, 30.5, 43.5 and 56.5 mm) from the bottom of the 120 jar. The temperature of fruit pieces was obtained by using five wire thermocouples (diameter = 0.9121 mm) inserted at the core of each fruit. The temperature at half the height of the outer wall of the jar 122 was also measured. Both for multipoint probe and single thermocouples, an acquisition rate of 2 s 123 was used and time-temperature data were collected in an Excel® ASCII worksheet.

124

# 125 **3. CFD modelling**

# 126 *3.1 Geometry of fruit salad in the glass jar*

127 The process of thermal treatment of fruit salad in a glass jar was simulated by means of a 128 multidimensional CFD (Computational Fluid Dynamic) model. The observed spatial placement of 129 the fruit salad inside the container was replicated in a 3D CAD model. In order to reduce the computational effort required by the solution of the CFD model, the spatial domain was assumed to
be symmetric with regard to two perpendicular planes through the vertical axis of the jar, hence
only a quarter of the jar needed to be simulated.

The fruit pieces were spatially arranged on a regular grid (8 rows evenly distributed over the full jar height), and the spacing carefully chosen in order to obtain a solid/liquid content ratio as close as possible to that measured in the experimental tests. The resulting spatial arrangement of the fruit pieces in the model of the jar is depicted in **Figure 2**.

The model geometry was then imported into the ICEM CFD® software (Canonsburg, Pennsylvania, USA) and discretized into an unstructured tetrahedrical mesh. The maximum element dimension was chosen taking into consideration the domain (solid, fluid and glass). The values of maximum element edge dimension for the different fruit pieces inside the jar, together with syrup and glass are reported in **Table 1**.

Following the approach used by Kiziltas et al. (2010) and Dimou et al. (2011), in order to reduce the complexity of multiphase fluid calculation, the headspace was not considered in the simulation assuming the jar completely filled with product.

In order to accurately calculate the flow field near the wall of the jar, six layers of flat prismatic wedge element were used for the discretization of the fluid domain. The optimal number of wall boundary layers needed to obtain an appropriate level of accuracy was identified by means of a layer-independence analysis, which suggested a value for the dimension of the first element near the wall equal to 0.04 mm with a height ratio of 1.2 between layers. The final mesh with solid and fluid elements consists of  $3 \times 10^6$  elements (**Figure 3**).

151

152 3.2 Numerical model

153 The evaluation of the field of fluid flow and thermal exchange occurring in the considered domain

154 due to natural convection required numerical solution of the generalized transport equations:

a) Continuity Equation

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho V) = 0 \tag{1}$$

156

160

b) Momentum Equation

158 
$$\frac{\partial \rho V}{\partial t} + \nabla \cdot (\rho V \cdot V) = \nabla \cdot (-p\delta + \mu (\nabla V + (\nabla V)^t)) + S_M$$
(2)

159 c) Energy Equation

$$\frac{\partial \rho h_{total}}{\partial t} - \frac{Dp}{Dt} + \nabla \cdot (\rho V h_{total}) = \nabla \cdot (k\Delta T) + S_E$$
(3)

161 Where *t* is the time, *V* is the velocity vector,  $\rho$  is the density, *p* is the pressure,  $\mu$  is dynamic 162 viscosity, *k* is thermal conductivity,  $h_{total}$  is the specific total enthalpy.

163 The software Ansys® CFX 14.5 (Canonsburg, Pennsylvania, USA) was chosen for the calculation. 164 Natural convection was modelled using the Boussinesq approximation, which uses a constant 165 density fluid model, but applies a local body gravitational force throughout the fluid that is a linear 166 function of thermal expansivity  $\beta$  and of the local temperature difference. The buoyancy source is 167 added to the momentum equation as follows:

168

$$S_{M} = -\rho_{REF}\beta(T - T_{REF}) \qquad (4)$$

169 Where  $\rho_{ref}$  and  $T_{ref}$  are the density and temperature at the boundary wall condition and g is the 170 gravitational force.

171 No internal energy source terms  $(S_E)$  were taken into account.

172

173 3.3 Boundary conditions

A uniform time varying temperature condition was applied to all the external surfaces of the jar and corresponded to that measured in the experimental tests. The value of initial temperature of fruit and syrup was 22°C, while the variation of the outer wall temperature with time during the heat treatment is showed in **Figure 4** (black dotted line). 178 Since the maximum Rayleigh number Ra, as estimated using the maximum temperature difference 179 and the maximum viscosity, remained lower than  $10^6$  during the whole thermal treatment, laminar 180 flow was adopted for all the simulations.

An adaptive time step option was used in order to maintain the Courant number lower than 1; the maximum time step of 0.5 s was reached during heating phase. High resolution advection schemes were adopted for all simulations, in order to achieve second order accuracy. The convergence criterion was defined as residual root mean square (RMS) value lower than 10<sup>4</sup>.

185

#### 186 *3.4 Thermal and physical properties*

Values of thermal and physical properties such as density ( $\rho$ ), viscosity ( $\mu$ ), specific heat (Cp) and thermal conductivity (k) of fruits, syrup and glass were needed for the definition of the model and the values used are summarized in **Table 1**. The viscosity of the syrup was assumed to be a function of temperature and a linear interpolation from experimental data was used.

191

#### 192 3.5 Model validation

193 The developed model was validated by comparing experimental temperature measurements at 194 specific points inside the glass jar with predicted ones. The accuracy of the model prediction was 195 assessed by determining root mean square error (*RMSE*) and lethality ( $F_0$ ). The equation for *RMSE* 196 determination can be expressed as:

$$RMSE = \sqrt{\frac{\sum_{i=1}^{n} (T_{E} - T_{P})^{2}}{N}}$$
(5)

197

198 where  $T_P$  is simulated temperature and  $T_E$  is measured temperature, at time *t*. The effect of heat 199 treatment and time with respect to the survival of a microorganism can be quantified by the 200 following *F* value equation (Holdsworth and Simpson, 2007):

$$F = \int_{0}^{T} 10^{(T - T_{ref})/z} dt$$
(6)

202 Lethality was calculated as an equivalent heating time at a constant temperature  $(T_{ref})$  of 90°C and a 203 z value of 10°C as characteristic for pathogenic microorganisms and *Clostridium botulinum* spores 204 (Padmavati and Anandharamakrishnan, 2013).

205

201

#### 206 **4. Results and discussion**

#### 207 4.1 Validation results

208 The simulation results were in agreement with the experimental data for both the syrup and the 209 fruits, as shown in Table 2, where validation parameters at each measurement point are reported (4 210 and 5 points for syrup and fruits, respectively). No significant differences were observed between 211 experimental and simulated F values, confirming the accuracy of the developed model. In addition, 212 in Figure 4 and 5 heating curves of the experimental treatment and simulation for syrup and fruit 213 pieces are compared, respectively. The small variations in the results of the model may be due to 214 the distribution of the fruit pieces, the combined effects of the experimental and model assumptions 215 such as Boussinesq approximation and the thermal properties of the materials. Furthermore, during 216 the experiment, the location of the temperature sensor may change the liquid flow pattern and 217 hence, affects the temperature profile of the sugar solution. In the simulation, small-scale 218 instabilities were produced by the buoyancy effect. The buoyancy-produced structures might have 219 directly interacted with the existing local turbulence with the strong coupling where laminar 220 modelling could not successfully predict this effect.

221

222 4.2 Slowest heating point (SHP) and temperature profile

The identification of the slowest heating point (SHP) inside the container was considered of basicimportance for the effectiveness of thermal processing of our samples. The temperature distribution

inside the jar was then measured at different time steps in order to describe the convectivemovement of the SHP.

227 When a fluid is subjected to a rapid temperature increase adjacent to a solid wall, part of the fluid in 228 the wall neighbourhood expands resulting in an increase in the local pressure with significant 229 effects in heat transfer due to thermal buoyancy effects in a gravitational force field (Aktas and 230 Farouk, 2003). In a similar way, during thermal processing of solid-liquid mixtures in cans, such as 231 canned fruit salad, syrup closer to the can walls receives the heat (undergoes heat flux) thus 232 resulting in volume expansion and density decrease while the syrup far from the walls is still at 233 lower temperature. This phenomenon leads to development of an upward buoyancy force with a 234 motion due to density differences. This movement also carries the colder fluid upward by viscous 235 drag. The fluid flowing upward is deflected by the top surface of the can and starts moving in a 236 radial direction and, by becoming heavier, starts to move downwards through the stack of fruits. 237 Consequently, its temperature decreases as it comes in contact with colder pieces of fruits and 238 syrup, and a new cycle starts from the bottom. These convective movements create a recirculating 239 flow thus increasing the rate of heat transfer. This observation is similar to the results obtained by 240 other Authors for natural convection heating mechanism (Ghani et al., 1999a; Padmavati and 241 Anandharamakrishnan, 2013). The maximum value of liquid velocity was observed close to the 242 wall of the jar (due to the higher temperature gradient between the jar wall and the thin liquid layer 243 close to the wall). When solid and impermeable particles were distributed into the fluid, the velocity 244 profile changed due to the heat exchange and surface deflections: the flow was very slow through 245 the stack of solid particles in the horizontal direction while on the contrary it showed an increase 246 between solids in the vertical direction.

In the case of pure convection heating of liquids, the slowest heating point (SHP) is located at about 10-15% of the can height (Padmavati and Anandharamakrishnan, 2013), but in the case of solidliquid food mixtures heated by a combination of conduction and convection, SHP location is more

complex to determine. Under our experimental conditions, the SHP of the canned fruit salad was not at the geometric centre of the can nor at a can height of 10-15% but at an intermediate position between these (19-20% of the can height). The position of SHP is well shown by the *F value* of the various fruits: pear pieces presented the lowest *F value* because this kind of fruit was positioned closer to the SHP.

The natural convection effects also influenced the heating of the fruit pieces. As shown in **Table 2**, the fruits positioned close to the top of the jar showed a simulated *F value* higher than those placed close to the bottom: grape = 8.80 min, peach = 4.16 min.

When there is a marked effect of natural convection heating, thermal stratification takes place (observation based on the fluid movement due to buoyancy effects explained above). **Figure 6** shows temperature stratification for the syrup during heating phase, at 4 different time steps (5, 10, 20 and 30 min), while **Figure 7** reports the temperature stratification along the fruit pieces at the same time steps (both figures come from the graphical representation of the mathematical model).

263

#### 264 **5.** Conclusions

In this study, a 3D CFD model was developed in order to investigate the temperature profiles, to identify the slowest heating point (SHP) and to describe the flow field during the heating processing of canned fruit salad composed of five kinds of fruit canned in a glass jar and filled with sugar syrup.

Experimental *F values* were different among the various fruits and in particular they were a function of position, dimension and thermal properties; moreover, experimental *F values* were also greatly influenced by the natural convection motion of the syrup.

272 Concerning the proposed model, an appreciable agreement between simulated and experimental 273 measurements of temperature both for syrup and fruit pieces was obtained: the model can be

- considered successfully validated and applicable for the simulation and prediction of thermalprocesses of canned fruit salad.
- 276 An increase in the reliability of the model by minimizing the differences with experimental data and
- by studying the influence of fruit position inside the jar during the thermal process can be achieved.

#### 278 **References**

- Akhijahani, H. S., Khodaei, J. (2013). Investigation of specific heat and thermal conductivity of
  rasa grape (*Vitis vinifera* L.) as a function of moisture content. *World Applied Sciences Journal*, 22,
  939-947.
- 282 Aktas, M.K., Farouk, B. (2003). Numerical simulation of developing natural convection in an
- enclosure due to rapid heating. International Journal of Heat and Mass Transfer, 46, 2253-2261.
- 284 Anandharamakrishnan, C. (2011). Applications of computational fluid dynamics in food processing
- 285 operations. In A. D. Murphy (Ed-), *Computational fluid dynamics: theory, analysis and*286 *applications-Chapter 9* (pp. 297-316). New York: Nova Publishers.
- ASHRAE, (2006). Thermal properties of foods. *Handbook refrigeration-Chapter 9*.
- Chen, C.R., & Ramaswamy, H.S. (2007). Visual basic computer simulation package for thermal
  process calculations. *Chemical Engineering and Processing*, 46, 603-613.
- Chhanwal, N., Tank, A., Raghavarao, K.S.M.S., & Anandharamakrishnan, C. (2012).
  Computational fluid dynamics applications in bread baking process. *Food and Bioprocess Technology*, 5, 1157-1172.
- Dimou, A., Yanniotis, S. (2011). 3D numerical simulation of asparagus sterilization in a still can
  using computational fluid dynamics. *Journal of Food Engineering*, 104, 394-403.
- Ghani, A. G., & Farid, M. M. (2006). Using the computational fluid dynamics to analyse the
  thermal sterilization of solid-liquid food mixture in cans. *Innovative Food Science and Emerging Technologies*, 7, 55-61.
- 298 Ghani, A. G., Farid, M. M., & Chen, X. D. (2002). Numerical simulation of transient temperature
- and velocity profiles in a horizontal can during sterilization using computational fluid dynamics.
- 300 Journal of Food Engineering, 51, 77-83.

- Ghani, A. G., Farid, M. M., Chen, X. D., & Richards, P. (1999a). Numerical simulation of natural
  convection heating of canned food by computational fluid dynamics. *Journal of Food Engineering*,
  41, 55-64.
- 304 Ghani, A. G., Farid, M. M., Chen, X. D., & Richards, P. (1999b). An investigation of deactivation
- 305 of bacteria in canned liquid food during sterilization using computational fluid dynamics (CFD).
- 306 Journal of Food Engineering, 42, 207-214.
- Holdsworth, D., Simpson, R. (2007). *Thermal processing of packaged foods, food engineering series*. New York: Springer.
- 309 Incropera, F. P, DeWitt D. P., Bergman T. L., Lavine, A. S. (2006). *Fundamental of heat and mass*310 *transfer*. John Wiley & Sons.
- 311 Kiziktas, S., Erdogdu, F., & Palazoglu, T.K. (2010). Simulation of heat transfer for solid-liquid
- food mixtures in cans and model validation under pasteurization conditions. *Journal of Food Engineering*, 97, 449-456.
- Kumar, A., Bhattacharya, M., & Blaylock, J. (1990). Numerical simulation of natural convection
  heating of canned thick viscous liquid food products. *Journal of Food Science*, 55, 1403-1411.
- 316 Kuriakose, R., & Anandharamakrishnan, C. (2010). Computational fluid dynamics (CFD)
- 317 applications in spray drying of food products. *Trends in Food Science and Technology*, 21, 383318 398.
- Norton, T., Sun, D.W. (2006). Computational fluid dynamics (CFD) an effective and efficient
  design and analysis tool for the food industry: A review. *Trend in Food Science & Technology*, 17,
  600-620.
- Padmavati, R., Anandharamakrishnan, C. (2013). Computational Fluid Dynamics Modeling of the
  Thermal Processing of Canned Pineapple Slices and Titbits. *Food Bioprocess Techology*, 6, 882895.

- Rabiey, L., Flick, D., & Duquenoy, A. (2007). 3D simulations of heat transfer and liquid flow
  during sterilization of large particles in a cylindrical vertical can. *Journal of Food Engineering*, 82,
  409-417.
- 328 Rahman, M.S. (2008). Food properties Handbook. Boca Raton: CRC.
- 329 Sun, D.W. (2007). Computational fluid dynamics in food processing. Boca Raton: CRC.
- Varma, M. N., & Kannan, A. (2005). Enhanced food sterilization through inclination of the
  container walls and geometry modifications. *International Journal of Heat and Transfer*, 48, 3753332 3762.
- 333 Weng, Z.J. (2005). Thermal processing of canned foods. In: Sun, Da-Wen (Ed.), Thermal Food
- 334 Processing-New Technologies and Quality Issues Chapter 11. Boca Raton: CRC-Taylor and
- 335 Francis.
- Whitelock, D.P., Brusewitz, G.H., Ghajar, A.J. (1999). Thermal/physical properties affect predicted
  weight loss of fresh peaches. *American Society of Agricultural Engineers*, 42, 1047-1053.
- 338 Xia, B., & Sun, D.W. (2002). Review: applications of computational fluid dynamics (CFD) in the
- 339 food industry. *Computers and Electronics in Agriculture*, 34, 5-24.















## **Captions for Figures and Tables**

Fig. 1 - Visual comparison of the different kind of fruits used in the experiments

Fig. 2 - 3D model of the distribution of the fruits inside the jar

Fig. 3 - 3D model of the fruits inside the jar with the mesh element

Fig. 4 - Comparison of temperature profile in syrup between experimental test and mathematical model

Fig. 5 - Comparison of the temperature profile in fruit pieces between experimental test and mathematical model

Fig. 6 - Temperature stratification of the syrup at 4 different time steps (from mathematical model)

**Fig. 7** - Temperature stratification of the fruit pieces at 4 difference time steps (from mathematical model)

**Table 1 -** Thermal properties, rheological characteristic and maximum element edge dimension for

 all the different kinds of fruit inside the jar, together with syrup and glass

Table 2 - Validation results

# Table 1

Food	$\rho$ (kg/m <sup>3</sup> )	μ (Pa s)	$C_p$ (J/kg K)	<i>k</i> (W/m K)	Max edge length <sup>g</sup> (mm)
Syrup (16,7% sugar)	1074 <sup>g</sup>	0,0258-0,00023*T <sup>g</sup>	-	-	0.50
Peach	930 <sup>a</sup>	-	3700 <sup>a</sup>	0.581 <sup>b</sup>	1.70
Pear	$1000^{b}$	-	$3800^{\circ}$	$0.595^{b}$	1.50
Pineapple	1010 <sup>d</sup>	-	3490 <sup>d</sup>	$0.549^{d}$	0.80
Grape	1320 <sup>c</sup>	-	3325 <sup>e</sup>	0.273 <sup>e</sup>	0.45
Cherry	1049 <sup>b</sup>	-	3730 <sup>c</sup>	0.511 <sup>c</sup>	0.26
Glass	$2500^{f}$	-	750 <sup>f</sup>	$1.400^{f}$	2.00

<sup>a</sup> from Whitelock et al. (1999); <sup>b</sup> from Rahman (2008); <sup>c</sup> from 2006 ASHRAE Handbook-refrigeration; <sup>d</sup> from Padmavati and Anandharamakrishnan (2013); <sup>e</sup> from Akhijahani and Khodaei (2013); <sup>f</sup> from Incropera et al. (2006); <sup>g</sup> experimental value.

Po	int of	RMSE	Lethality (F <sub>90,10</sub> )			
measi	urement		Experimental	Simulated	$\varDelta F_{90,10}$	
	17,5 mm	0.68	0.17	0.14	0.02	
	30,5 mm	0.79	0.66	0.52	0.14	
Syrup	43,5 mm	1.77	1.68	1.62	0.05	
	56.5 mm	2.65	2.99	3.73	0.73	
	Average	1.47			0.13	
Peach		1.14	4.24	4.16	0.07	
Pear		2.31	0.95	0.96	0.02	
Pineapple		1.78	4.04	4.13	0.09	
G	rape	1.61	8.87	8.80	0.06	
Cł	nerry	1.31	6.24	6.27	0.03	
	Average	1.63			0.06	

# Table 2